

Optional Iron-on Horsepower Application Instructions

Apply before using the cover.

Please follow the steps below if you would like to add the option HP numbering to your cover. We have supplied a small additional swatch of fabric to practice (please use one of the numbers you do not need) prior to applying the actual number to your cover. We strongly suggest you do a trial as once applied the lettering cannot be removed.

- Set a standard domestic iron to the medium heat setting (1/2 way on the dial which is between WOOL SILK on most irons).
 IMPORTANT:- TURN OFF ANY STEAM SETTINGS.
- 2. The cover has a chalk line on the rear showing where the HP NUMBERS should be applied. Place this section on the end of the ironing board making sure the fabric is flat & crease free.
- 3. Gently iron over the area where the numbers are to be attached. This will remove any residual moisture. TAKE CARE NOT TO IRON OVER ANY STITCHING, MESH, ELASTIC or PRINTING (including OCA Logo).
- 4. Select the required HP and align the bottom of the numbers with the chalk line. **DO NOT REMOVE THE PROTECTIVE CLEAR FILM.**
- 5. Once you are happy with the position and alignment you can use the iron to attach the numbers.
- 6. Use a medium pressure and move the iron from side to side for 15-20 seconds. Make sure you apply even pressure to the entire transfer.
- ALLOW TO COOL BEFORE PEELING the clear protective film gently back. If the numbers appear to lift, stop peeling, replace the film and repeat from step 5 above. You may need to increase the temperature and pressure SLIGHTLY.
- 8. Once cooled, clean any residual chalk marks off the fabric with a damp cloth.

DO NOT APPLY HEAT TO THE NUMBERS WITHOUT THE PROTECTIVE FILM.

To see our on line tutorial visit our http://www.outboardcovers.com/resources.htm

Outboard Covers & Accessories Pty Ltd. Unit 2/ 12-14 Stanhope Gardens, Midvale, Western Australia, 6056 www.outboardcovers.com



Below is an example of what the print will look like if you have your iron settings too LOW. - The logo will peel very easily, if this happens repeat from step 6 above.

Too LONG/ HOT and you will burn the print media.